

T0435H-8C 4A TRIAC


Rev.A.1.1

DESCRIPTION:

The T0435H-8C triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. Compared to traditional triacs, T0435H-8C provides a very high switching capability up to junction temperatures of 150°C. From T2 terminals to external heatsink. Package TO-220C is RoHS compliant.

MAIN FEATURES

Symbol	Value	Unit
$I_{T(RMS)}$	4	A
V_{DRM}/V_{RRM}	800	V
$I_{GT\ I/II/III}$	35/35/35	mA


ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	°C
Operating junction temperature range	T_j	-40-150	°C
Repetitive peak off-state voltage ($T_j=25^\circ\text{C}$)	V_{DRM}	800	V
Repetitive peak reverse voltage ($T_j=25^\circ\text{C}$)	V_{RRM}	800	V
RMS on-state current ($T_c \leq 140^\circ\text{C}$)	$I_{T(RMS)}$	4	A
Non repetitive surge peak on-state current (full cycle , $t_p=20\text{ms}$, $T_j=25^\circ\text{C}$)	I_{TSM}	40	A
Non repetitive surge peak on-state current (full cycle , $t_p=16.6\text{ms}$, $T_j=25^\circ\text{C}$)		44	
I^2t value for fusing ($t_p=10\text{ms}$, $T_j=25^\circ\text{C}$)	I^2t	8	A^2s
Critical rate of rise of on-state current ($I_G=2 \times I_{GT}$, $f=100\text{Hz}$, $T_j=150^\circ\text{C}$)	di/dt	80	$\text{A}/\mu\text{s}$
Peak gate current ($t_p=20\mu\text{s}$, $T_j=150^\circ\text{C}$)	I_{GM}	4	A
Average gate power dissipation ($T_j=150^\circ\text{C}$)	$P_{G(AV)}$	1	W
Peak gate power	P_{GM}	10	W

Peak pulse voltage ($T_j=25^{\circ}\text{C}$; non-repetitive, off-state; FIG.7)	V_{pp}	4	kV
--	----------	---	----

ELECTRICAL CHARACTERISTICS ($T_j=25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	$V_D=12\text{V}$ $R_L=33\Omega$	I - II -III	MAX.	35	mA
V_{GT}		I - II -III	MAX.	1	V
V_{GD}	$V_D=V_{DRM}$ $T_j=150^{\circ}\text{C}$ $R_L=3.3\text{k}\Omega$	I - II -III	MIN.	0.2	V
I_L	$I_G=1.2I_{GT}$	I -III	MAX.	40	mA
		II		50	
I_H	$I_T=100\text{mA}$		MAX.	30	mA
dV/dt	$V_D=540\text{V}$ Gate Open $T_j=150^{\circ}\text{C}$		MIN.	1000	V/ μs
$(dI/dt)_c$	$(dV/dt)_c=20\text{V}/\mu\text{s}$, $T_j=150^{\circ}\text{C}$		MIN.	8	A/ms
t_{on}	$I_G=40\text{mA}$ $I_A=200\text{mA}$ $I_R=20\text{mA}$ $T_j=25^{\circ}\text{C}$		TYP.	3	μs
t_{off}				30	

STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX.)	Unit
V_{TM}	$I_{TM}=5.5\text{A}$ $t_p=380\mu\text{s}$	$T_j=25^{\circ}\text{C}$	1.4	V
V_{TO}	Threshold voltage	$T_j=150^{\circ}\text{C}$	0.6	V
R_D	Dynamic resistance	$T_j=150^{\circ}\text{C}$	129	$\text{m}\Omega$
I_{DRM}	$V_D=V_{DRM}$ $V_R=V_{RRM}$	$T_j=25^{\circ}\text{C}$	5	μA
I_{RRM}		$T_j=150^{\circ}\text{C}$	1	mA

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	junction to case (AC)	2	$^{\circ}\text{C}/\text{W}$
$R_{th(j-a)}$	junction to ambient (AC)	60	$^{\circ}\text{C}/\text{W}$

ORDERING INFORMATION

T	04	35	H	-8	C
Triacs					C:TO-220C
IT(RMS):4A					
		35:IGT1-3≤35mA		8:VDRM /VRRM≥800V	
			High junction temperature		

MARKING


	XXX XXX Year _____ Production Code _____ Month _____
---	---

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.3: Surge peak on-state current versus number of cycles




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 20\text{ms}$, and corresponding value of I^2t ($di/dt < 80\text{A}/\mu\text{s}$)




FIG.2: RMS on-state current versus case temperature




FIG.4: On-state characteristics




FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature





FIG.7: Test circuit for inductive and resistive loads to IEC-61000-4-5 standards



LEAD FORMING AND SOLDERING

Refer to the application note "Assembly Instructions for Thyristors in Through-hole Package" released by JieJie Microelectronics

ORDERING INFORMATION

Order code	Voltage $V_{\text{DRM}}/V_{\text{RRM}}$ (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		I - II - III			
T0435H-8C	800	35	TO-220C	50	Tube

Document Revision History

Date	Revision	Changes
Apr.10, 2023	A.1.0	Last updated
Oct.14, 2025	A.1.1	Revise PACKAGE MECHANICAL DATA

Technical drawing of a 3-pin industrial plug, showing three views: front, side, and top.

Front View (Left): Shows the main body of the plug. Dimensions include:

- E:** Total width of the main body.
- L:** Distance from the left edge to the center of the top hole.
- L3:** Height of the top section.
- H:** Total height of the main body.
- L1:** Height of the top section.
- K:** Height of the middle section.
- L2:** Diameter of the three pins.
- B:** Width of the pin base.
- G:** Distance from the bottom of the main body to the base of the pins.
- M:** Total width of the pin base.

Side View (Right): Shows the profile of the plug. Dimensions include:

- A:** Width of the top section.
- C2:** Distance from the left edge to the center of the top hole.
- E:** Total width of the main body.
- D:** Height of the middle section.
- C3:** Distance from the right edge to the center of the top hole.
- C:** Width of the pin base.

Top View (Bottom): Shows the top of the plug. Dimensions include:

- E1:** Width of the top section.
- H1:** Height of the top section.

Notes:

- A dimension line indicates a hole diameter of $\varnothing 3.45-3.65\text{mm}$.
- Red dashed lines indicate center lines for the top hole and the three pins.

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.70		0.90	0.028		0.035
C	0.45		0.60	0.018		0.024
C2	1.25		1.35	0.049		0.053
C3	2.20		2.60	0.087		0.102
D	8.90		9.90	0.350		0.390
E	9.90		10.30	0.390		0.406
E1	0.80		1.20	0.031		0.047
F	6.30		6.90	0.248		0.272
G	2.40		2.70	0.094		0.106
H	28.00		29.80	1.102		1.173
H1	2.15		2.55	0.085		0.100
I	4.70		5.10	0.185		0.201
K	9.90		10.30	0.390		0.406
L1	2.70		3.30	0.106		0.130
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
M	4.80		5.20	0.189		0.205

Technical drawing of a 3D printed part, showing three views: top, front, and side views. The dimensions are specified in millimeters (mm).

Top View Dimensions:

- Overall width: 520 ± 0.5
- Overall height: 530 ± 0.5
- Printing area width: 80
- Printing area height: 5.5
- Distance from left edge to printing area: 5
- Distance from top edge to printing area: 3
- Distance from right edge to printing area: 5
- Distance from bottom edge to printing area: 5.5
- Distance from left edge to printing area: 520
- Distance from top edge to printing area: 3
- Distance from right edge to printing area: 5
- Distance from bottom edge to printing area: 5.5
- Distance from left edge to printing area: 520
- Distance from top edge to printing area: 3
- Distance from right edge to printing area: 5
- Distance from bottom edge to printing area: 5.5

Front View Dimensions:

- Overall width: 520 ± 0.5
- Overall height: 530 ± 0.5
- Printing area width: 80
- Printing area height: 5.5
- Distance from left edge to printing area: 5
- Distance from top edge to printing area: 3
- Distance from right edge to printing area: 5
- Distance from bottom edge to printing area: 5.5
- Distance from left edge to printing area: 520
- Distance from top edge to printing area: 3
- Distance from right edge to printing area: 5
- Distance from bottom edge to printing area: 5.5
- Distance from left edge to printing area: 520
- Distance from top edge to printing area: 3
- Distance from right edge to printing area: 5
- Distance from bottom edge to printing area: 5.5

Side View Dimensions:

- Overall width: 7 ± 0.2
- Overall height: 33
- Printing area width: 3.8
- Printing area height: 0.6
- Distance from left edge to printing area: 2.4
- Distance from top edge to printing area: 3.8
- Distance from right edge to printing area: 3.8
- Distance from bottom edge to printing area: 0.6
- Distance from left edge to printing area: 2.4
- Distance from top edge to printing area: 3.8
- Distance from right edge to printing area: 3.8
- Distance from bottom edge to printing area: 0.6
- Distance from left edge to printing area: 2.4
- Distance from top edge to printing area: 3.8
- Distance from right edge to printing area: 3.8
- Distance from bottom edge to printing area: 0.6

PACKAGE	OUTLINE	TUBE (PCS)	INNER BOX (PCS)	PER CARTON
TO-220C	TUBE	50	1,000	5,000

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.